Rocket Flight Check List

A. Complete Motor Base with Cargo Unit

- 1. Check separation between cargo and motor base (booster). It should be easy to separate but not fall off. Use baby powder to help.
- 2. Insert motor, make sure it is clipped in, don't forget the spacer, tape around the end, be careful with igniter.
- 3. Put a little 'dog barf' in the top of the motor mount, on top of the motor ejection charge, use a stick to insert.
- 4. Baby powder the chutes, fold parachute in loose "z" format, but never wrap shrouds around chuts.
- 5. Insert chute protector over the motor mount.
- 6. Insert chutes, snake the shrouds loosely on top of the chutes, Pack shock cords loosely; use baby powder to keep it loose.
- 7. Close up cargo on motor base.

B. Cargo Unit Setup

- 1. Put eggs in plastic bag. Insert eggs in nose cone with foam protection.
- 2. Turn on altimeter. Insert altimeter and holder into cargo unit, use foam pads to keep holder tight. You have **20 seconds** to do this. Do not let the sun shine on the altimeter.
- 3. Be careful not to trip the altimeter sensor, be sure it has access to air holes.
- 4. Place nose cone on cargo. Follow alignment marks. Do not push nose cone on sharply because it may trip the altimeter.
- 5. Shake rocket lightly to be sure nothing rattles around and cargo (eggs) are secured.
- 6. Listen for altimeter in ready beeping state. If tripped, go back to number 2.
- 7. Check in, weigh the rocket and record the grams. You may need to weigh the cargo unit separately.

C. Load on Launch Tower

- 1. WD40 and steel wool launch rod/rail.
- 2. Load on tower, be sure it is loose and can move up tower.
- 3. Angle launch rod with the wind, one degree for every mile per hour of wind.
- 4. Use a plum bob to check the angle and direction.
- 5. Connect launch power line clips.
- 6. One last look. Ask a buddy to check.
- 7. If you think you have a problem or forgot something Stop Now.

D. Launch

- 1. Clear launch area. Send out recovery team.
- 2. Check if photographers ready. Check if timers ready.
- 3. Tell range safety officer OK for launch, signal ready to launch.

E. Recovery

- 1. Recovery team needs to walk/run to landing area before it lands. **Don't catch.**
- 2. Carefully pick up cargo unit do not remove eggs or altimeter. Just listen.
- 3. Don't forget the booster.
- 4. Take rocket (everything) to officials for evaluation.
- 5. Remove egg and altimeter with officials watching.